

Q. P. Code: 22931

(3 Hours)

[Total Marks: 80]

- N. B.: (1) Question No. 1 is compulsory.
  - (2) Attemt any three questions from remaining questions.
  - (3) Assume suitable data if necessary.
- 1. (a) Define static characteristics of an instrument.
  - a) Define static characteristics of an instrument.
  - (b) Compare open loop and closed loop control system with block diagram

    4

    (c) Derive an expression for the resistance using Wheastone bridge for balanced
  - (c) Derive an expression for the resistance using Wheastone bridge for balanced condition.
  - (d) Compare analog and digital data acquisition system.
  - (e) Explain Hurwitz stability criterion.
- (a) Mention the sources of error in Q meter. Explain how Q meter is used to measure 10 the high impedance
  - (b) A second order system is given by

$$\frac{C(S)}{R(S)} = \frac{25}{S^2 + 5S + 25}$$

Find delay time, rise time, peak time, peak overshoot, settling time. Also find expression for its output response.

3. (a) The open loop transfer function of a unity feedback system is given by

$$G(S) = \frac{K}{S(S+4)(S+6)}$$

Sketch the Root locus of the system.

(b) Draw the bode plot for the given transfer function with unity feedack 10

$$G(S) = \frac{0.75(1 + 0.2S)}{S(1 + 0.5S)(1 + 0.1S)}$$

Calculate gain margin, phase margin and comment on stability.

TURN OVER


4 (a) I) Explain basic telemetry system

- 5
- Using Routh stability criterion determine the stability of the system whose characteristic equation is

5

$$S^6 + 2S^5 + 8S^4 + 12S^3 + 20S^2 + 16S + 16$$

- (b) Explain the working principle of LVDT with neat diagram and explain advantages 10 and disadvantages of LVDT
- Draw signal flow graph for the system shown below. Find overall transfer function 10 C(S)/R(S) using Mason's gain formula.



- (b) Define power and energy. Explain the working of Electrodynamometer wattmeter. 10
- 6 (a) I) Explain digital data acquisition system.

5

II) Define the following parameters

5

- Transient response
- ii. Steady state response
- iii. define Type 0, Type 1, Type 2 system
- (b) I) Compare temperature transducer with respect to their characteristics and measurement range.
- II) What are the advantages of polar plot. Draw the polar plot of the given transfer function

$$G(S) = \frac{10}{(s+2)}$$

-----

Page 2 of 2